

CASIO® TE-2400

Simple, yet powerful cash register to help you manage your hospitality business transactions



www.casio.co.uk/systems

CASIO®

The Casio TE-2400 features a 77 key fully flat keyboard for fast order registering, high speed dual printers and a bright customer display making it ideal for the hospitality environment.

CASIO® TE-2400

Receipt and journal printer



The TE-2400's two fast, 58mm wide thermal printers can print at up to 14 lines per second. To give your business a professional appearance, graphic logos and watermarks can also be printed. With easy drop-in paper loading for roll replacement, the TE-2400 ensures fast and efficient operation.

Table control function

A basic table control function is provided for small restaurants, cafes and bars. Purchased items can be input against a table number, allowing easy check tracking.

By attaching the TE-2400 to a remote kitchen printer, food orders can automatically be printed in the kitchen, maximising order preparation time.

Barcode scanning

The TE-2400 supports barcode scanning. This allows up to 5000 products to be scanned into the cash register, ensuring items are sold at the correct price and eliminating the need to manually enter prices.

Display

A bright, contrast adjustable 5.2-inch LCD operator display with large price display and 2 lines for other product information, means your staff can easily see the details of the items they are selling. A standard pop-up rear display ensures your customers can see the price they are paying, giving them peace of mind.



Help function

The TE-2400 is simple to operate, however there is also a user friendly "HELP" button on the keyboard. Answers to frequently asked questions such as how to programme the time and date can be printed on the receipt printer for easy reference.



Peripherals

For maximum flexibility, the TE-2400 features two serial ports for direct connection to PC, modem, printers or scanners.

Reports and useful functions

Daily reports can be printed on the TE-2400 using compressed printing. Other useful functions include clerk interrupt, scheduler function, set menu function, arrangement function and memory allocation.

- Financial
- Transaction
- Department
- PLU
- PLU stock
- Table analysis
- Open check
- Monthly
- Hourly
- Flash
- Group
- Clerk
- Time & attendance
- Scanning PLU
- Scanning PLU stock
- Inactive PLU

| | | | |
|-------------|----------------|------------|--|
| Z | 10-10-2012 | 21:10 | Mode symbol/date/time |
| C01 | MC#01 | 000045 | Clerk descriptor/Mc-No./consecutive No. |
| Z | SCAN PLU | 0001 | Report header/title/reset counter (Z only) |
| | | 2001026 | Report code |
| DEPT01 | |01 | Classified title(by group/dept) |
| SCAN_PLU001 | | 382 | Scanning PLU character/quantity |
| | | 17.07% | Sales ratio/total |
| | #4901234567894 | | Scanning PLU code |
| SCAN_PLU002 | | 382 | |
| | | 38.01% | |
| | #4989012345674 | | |
| SCAN_PLU003 | | 382 | |
| | | 10.49% | |
| | #4967890123454 | | |
| | | 1253 | Total of this classification |
| | | 9,275.83 | |
| DEPT02 | |02 | |
| SCAN_PLU010 | | 453 | |
| | | 1,583.47 | |
| | #4945678901234 | | |
| | | 243 | |
| | | 10,375.93 | |
| TL | | 12653 | Quantity total |
| | | 273,375.93 | Amount total |

Data storage

The TE-2400 features a Compact Flash (CF) card slot, which allows reports to be saved to a CF card for easy transferral to PC for manipulation with other software. Program data can also be stored for backup purposes.

Options

| Model No. | Product |
|-----------|----------------------------|
| SP-1300 | Slip Printer |
| UP-360 | External Printer (thermal) |

Specifications

| | |
|-----------------------------|---|
| Operator | 5.2-inch backlit LCD |
| Displays | 2 x 16 characters / 10 digits, 7 segments |
| Customer | Pop-up 8-digit numeric |
| Printer | Printing method Two-station thermal printer |
| | Printing speed 14 lines/sec. (max.) |
| | Paper width 58mm +0/-1mm x 80 |
| | Paper loading Drop-in paper loading |
| Memory back-up | 90-day data backup (vanadium lithium battery) |
| Power consumption | AC 230V: Operating 0.25A, Standby 0.05A |
| Operating environment | Temperature: 0 to 40°C |
| | Humidity: 10 to 90%RH |
| Dimensions (w/ med. drawer) | 277 (H) x 400 (W) x 450 (D) mm |
| Weight (w/ med. drawer) | Approx. 12 kg |

Specifications and design are subject to change without notice