

CASIO®

TE-3000S TE-4000F TE-4500F

Stylish EPOS terminals with flexible keyboard programming and a 5-colour backlit LCD screen to suit your specific business needs



CASIO 

TE-3000S TE-4000F TE-4500F

Equipped with a full range of advanced features to complement and expand your business

System configuration

A maximum of 32 terminals can be connected to consolidate sales data. Shared check tracking by up to 4 terminals and printer sharing up to 3 external printers can be set up easily using CAT5 or CASIO inline cables. (Optional Arc-net communication board required.)

Operator display

5.2-inch LCD with 2 x 16 characters ensuring the operator a clear view of all transaction information. 10 digit, 7 segment display space for numeric entries. 5-colour backlight enabling the operator to select a display illumination colour to suit the store image. Scheduler function permitting switching among both backlight colours and menu levels to differentiate items or prices (between Lunch and Dinner menus, for example).



Tilt screen operator display

Tilt screen function allows the operator to adjust the display to the optimal angle for comfortable readability.



Printer

Silent 58mm thermal receipt and journal printer with fast line printing. Receipt auto cutter installed. Drop-in paper loading for easy paper roll handling. Graphic/watermark logos presenting an affluent image.



Data storage

CF (Compact Flash) card interface for data back-up and installed as standard equipment.



Serial ports

3 x RS232c ports for direct communication with computer, modem and external and slip printers. Com2 with +5v power provided for optional barcode scanner.

Scanning

Barcode scanning for quick, accurate registration available with optional barcode scanner.

Keyboards

TE-3000S: raised keyboard; TE-4000F: combination keyboard with reversible flat keyboard; TE-4500F: full flat keyboard.

Reports

- Financial
- Transaction
- Department, sub-department PLU
- Table analysis
- Open check
- Monthly
- Hourly, hourly item
- Employee (time and attendance)
- Flash
- Group
- Clerk
- Scanning PLU
- Mix & match
- Not-found PLU

Z	10-10-2010 SUN 21:10	Mode symbol/date/time
K	SMITH MCH01 000045	Clerk descriptor/Mc-No./consecutive No.
Z	SCAN PLU 0001	Report header/title/reset counter(Z only)
	2001020	Report code
DEPT0101	Classified title/by group/sub-dept
SCAN_PLU001	382	Scanning PLU character/quantity
#4901234567894	1,083.47	Sales ratio/total
SCAN_PLU002	382	Scanning PLU code
38.01%	3,576.46	
#4989012345674	382	
SCAN_PLU003	382	
10.49%	473.45	
#4967890123454		
	1253	Total of this classification
	5,275.83	
DEPT0202	
SCAN_PLU010	483	
	1,583.47	
#4949678901234		
	24.3	
	10,375.93	
TL	12653	Quantity total
	275,375.93	Amount total

Options

Model No.	Product
RK-3	1MB memory module
I/O-PB-17	Arc-net communication board
UP-360	External thermal printer
SP-1300	Slip printer

Specifications

Displays	Operator	5.2-inch LCD with color backlight 2 x 16 characters / 10 digits, 7 segments
	Customer	Pop-up 10-digit numeric LED
	Printing method	Two-station thermal printer
Printer	Printing speed	20 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 83 φ
	Receipt auto cutter	Yes
	Paper-loading	Drop-in paper-loading
Memory backup		90-day data back-up (vanadium lithium battery)
Power	AC 120V	Operating 0.9A, Standby 0.2A
consumption	AC 230V	Operating 0.5A, Standby 0.11A
Operating environment	Temperature	0 to 40 °C
	Humidity	10 to 85%RH
Dimensions (W x D x H)		410 x 491 x 215(292)*mm
Weight		Approx. 9 kg



www.casio.co.uk

CASIO

CASIO

CASIO ELECTRONICS CO. LTD, LONDON, UK

Specifications and design are subject to change without notice.